



Encrypted updates

1 **Contents**

2 **Threat model** **2**

3 Objectives 2

4 Properties 2

5 Threats 2

6 Mitigations 3

7 Risks and impacts 3

8 the private key for signing is leaked 3

9 the private key for signing is lost 3

10 the symmetric key for encryption/decryption is leaked 4

11 the symmetric key for encryption/decryption is lost 4

12 **Key infrastructure** **4**

13 How keys can be stored on devices 5

14 How keys can be deployed to devices 5

15 When new keys should be generated 5

16 How the build pipeline can fetch the keys 5

17 How multiple keys can be used for key rotations 5

18 How to handle the leak of a key to the public and how that impacts

19 future updates 6

20 **Encryption Parameters** **6**

21 The encryption of the update file makes accessing its contents more difficult for
22 bystanders, but doesn't necessarily protect from more resourceful attackers that
23 can extract the decryption key from the user-owned device.

24 The bundle encryption is done using the loop device with standard/proven kernel
25 facilities for de/encryption (e.g. dm-crypt/LUKS). This allows the mechanism
26 to be system agnostic (not tied to OSTree bundles), and can be used to ship up-
27 dates to multiple components at once by including multiple files in the bundle.
28 dm-crypt is the Linux kernel module which provides transparent encryption of
29 block devices using the kernel crypto API, see [dm-crypt](https://gitlab.com/cryptsetup/cryptsetup/-/wikis/DMCrypt)¹.

30 LUKS is the standard for Linux hard disk encryption. It provides secure man-
31 agement of multiple user passwords, see [LUKS wiki](https://gitlab.com/cryptsetup/cryptsetup/-/wikis/home)².

32 The authenticity of the update is checked by verifying the OSTree signature as
33 dm-crypt utilises symmetric cryptography which can't be used to ensure trust
34 as the on-device key can be used to encrypt malicious files, not just decrypt
35 them.

¹<https://gitlab.com/cryptsetup/cryptsetup/-/wikis/DMCrypt>

²<https://gitlab.com/cryptsetup/cryptsetup/-/wikis/home>

36 **Threat model**

37 **Objectives**

- 38 1. end-users can download updates from the product website and apply them
- 39 offline to the device via a USB key or SD card
- 40 2. only official updates should be accepted by the device
- 41 3. the contents of the updates should not be easily extracted, increasing
- 42 the effort required for an attacker and providing some protection for the
- 43 business' intellectual property

44 **Properties**

- 45 1. **integrity**: the device should only accept updates which have not been
- 46 altered
- 47 2. **authenticity**: the device should only accept updates coming from the
- 48 producer
- 49 3. **confidentiality**: the contents of the updates should not be disclosed

50 **Threats**

- 51 1. Alice owns a device and wants to make it run her own software
- 52 2. Emily owns a device and Alice wants to have her own software on Emily's
- 53 device
- 54 3. Vincent develops a competing product and wants to gain insights into the
- 55 inner workings of the device

56 **Mitigations**

- 57 1. **integrity**: the update is checksummed, causing alteration to be detectable
- 58 2. **authenticity**: the update is signed with a private key by the vendor
- 59 and the device only accepts updates with a signature matching one of the
- 60 public keys in its trusted set
- 61 3. **confidentiality**: the update is encrypted with a symmetric key (due to
- 62 technology limitations public key decryption is not available)

63 **Risks and impacts**

64 **the private key for signing is leaked**

65 **Impact**

- 66 • the private key allows Alice to generate updates that can be accepted by
- 67 all devices

68 **Mitigations**

- 69 • the private key is only needed on the vendor infrastructure producing the
70 updates
71 • the chance of leaks is minimized by securing the infrastructure and ensuring
72 that access to the key is restricted as much as possible
73 • public keys for the leaked private keys should be revoked
74 • multiple public keys should be trusted on the device, so if one is revoked
75 updates can be rolled out using a different key
76 • keys should not be re-used across products to compartmentalize them
77 against leaks

78 **the private key for signing is lost**

79 **Impact**

- 80 • updates can't be generated if no private key matching the on-device public
81 ones is available

82 **Mitigations**

- 83 • if multiple public keys are trusted on the device, the private key used can
84 be rotated if another private key is still available
85 • backup private keys should be stored securely in different locations

86 **the symmetric key for encryption/decryption is leaked**

87 **Impact**

- 88 • Alice has access to all symmetric keys stored in bundles encrypted with
89 the leaked key
90 • the symmetric key allows Alice to generate updates that can be decrypted
91 by devices

92 **Mitigations**

- 93 • due to its symmetric nature, the secret key has to be available on both
94 the vendor infrastructure and on each device
95 • secure enclave technologies can help use the symmetric key for decryption
96 without exposing the key in any way
97 • if secure enclave is not available the key has to be stored on the device
98 and can be extracted via physical access
99 • if the key can't be provisioned in the factory the key has to be provisioned
100 via unencrypted updates, from which an attacker can extract the keys
101 without physical access to the device
102 • multiple decryption keys must be provisioned, to be able to rotate them
103 in case of leaks

104 **the symmetric key for encryption/decryption is lost**

105 **Impact**

- 106 • encrypted updates can't be generated for devices only using this symmetric
107 key

108 **Mitigations**

- 109 • given that the key has to be available on each device, the chance of losing
110 the encryption/decryption key is small
111 • if multiple decryption keys are provisioned on the device, the encryption
112 key can be rotated
113 • if all keys are lost or corrupted on the device, it will not be possible to
114 decrypt bundles on USB/SDCard and so to update the device using this
115 method.

116 **Key infrastructure**

117 LUKS is able to manage up to 8 key slots, any of the 8 different keys can be
118 used to decrypt the update bundle. This can allow a bundle to be read using a
119 main key or fallback key(s), and/or by different devices with a different subsets
120 of the used keys.

121 On the device itself, Apertis Update Manager is in charge of decrypting the
122 bundle and it will try as many keys as needed to unlock the bundle, there's no
123 limitation on the number of keys which can be stored.

124 Random keys for bundle encryption can be generated using:

```
1     head -c128 /dev/random | base64 --wrap=0
```

125 **How keys can be stored on devices**

- 126 • Keys can be stored in separated files, located in read-only part of the
127 filesystem: `/usr/share/apertis-update-manager/`
128 • In future versions, keys may be stored using the secure-boot-verified key
129 storage system

130 **How keys can be deployed to devices**

- 131 • Keys stored in the filesystem can be deployed by the normal update mech-
132 anism

133 **When new keys should be generated**

134 New keys should be generated:

- 135 • for new products
- 136 • when a key has been compromised

137 **How the build pipeline can fetch the keys**

- 138 • As for the signing key, the key(s) used to encrypt the static delta bundle
139 should be passed to the encryption script GitLab CI/CD variable(s)

140 **How multiple keys can be used for key rotations**

- 141 • When the keys are stored on the filesystem, key rotation will not provide
142 any benefit as the leak of one key implies the leak of the others
- 143 • When the keys will be stored using the secure-boot-verified key storage
144 system, the encrypted updates will be generated with non-leaked keys and
145 will remove the leaked keys while adding the new keys to the secure-boot-
146 verified key storage system, so the number of available keys remain the
147 same

148 **How to handle the leak of a key to the public and how that 149 impacts future updates**

- 150 • If the keys are stored on the filesystem, the leak of one key implies the
151 leak of the others
- 152 • If the keys are stored using the secure-boot-verified key storage system,
153 the next update should be signed with a key that hasn't been leaked and
154 the update should revoke the leaked key

155 **Encryption Parameters**

156 In a classical usage, the encryption is setup through a benchmark on the
157 computer/board which will use it, allowing a good balance between password
158 strength and unlocking time. This could end-up by encrypted file not usable
159 due to out of memory error or slow unlocking time.

160 LUKS key strength is managed through 3 `cryptsetup` parameters: `--pbkdf-`
161 `memory`, `--pbkdf-force-iterations` and `--pbkdf-parallel`.

162 `--pbkdf-parallel` configures the maximum number of threads used to unlock the
163 encrypted file. This is automatically decreased on hardware devices that have
164 only one of just a few cores.

165 As encrypted update file is created during image build on computer with more
166 CPU power and memory, and that it is important to find a balance between pass-

167 word strength and usability, the `--pbkdf-memory` and `--pbkdf-force-iterations`
168 should be forced to appropriate values for the target board.